Series Click-Torque

Adjustable torque wrenches

Click-Torque A 5 torque wrench with reversible ratchet






Application: For clockwise torque-control

Precision: \pm 4% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: With ¼" square drive, reversible ratchet, 45 teeth; easy setting and saving of the desired torque value, with audible and tactile locking when the

scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle



Click-Torque A 6 torque wrench with reversible ratchet







Application: For clockwise torque-control

Precision: \pm 4% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: With ¼" hex drive, reversible ratchet, 45 teeth; easy setting and saving of the desired torque value, with audible and tactile locking when the scale

values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

			 [- 	 		0= 1	•		♦	- d	○	0==		†	
		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm						
05 075605 001	1/ "	2,5-25	0,10	1-18	290	121	42	25	11,5	11 ²⁷ / ₆₄ "	4 49/_"	1 ²¹ / ₃₂ "	1"	⁷ / ₁₆ "	