Series Click-Torque

Adjustable torque wrenches

Click-Torque C 3 torque wrench with reversible ratchet





Application: For clockwise torque-control

Precision: \pm 3% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: With 1/2" square drive, reversible ratchet, 45 teeth; easy setting and saving of the desired torque value, with audible and tactile locking when the

scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

	0	 			مُعِينًا مُعَالِمًا مُعَالِمًا مُعَالِمًا مُعَالِمًا مُعَالِمًا مُعَالِمًا مُعَالِمًا مُعَالِمًا مُعَالِمًا م	o===	○		†	مُعَاثِثُ الْعَادِثُ	0====	0=		♦ □
		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05 075622 001	1/_"	40-200	1,0	30-146	510	140	47	43	18,5	20 5/64"	5 ³³ / ₆₄ "	1 27/32"	1 11/1"	45/ "

Click-Torque C 4 torque wrench with reversible ratchet





Application: For clockwise torque-control

Precision: \pm 3% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: With 1/2" square drive, reversible ratchet, 45 teeth; easy setting and saving of the desired torque value, with audible and tactile locking when the

scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

	0	 	'''!ַ'			o==	-		†		0====	• 		♦ □
		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05 075623 001	1/2"	60-300	1,0	45-220	595	140	47	43	18,5	23 27/64"	5 ³³ / ₆₄ "	1 ²⁷ / ₃₂ "	1 ¹¹ / ₁₆ "	45/ " 64